

# HC SMOOTH STRIPNAIL 3,1X90MM CARBON STEEL STANDARD TENSILE



## HC59APBKR

### APPLICATIONS

Framing, pallets and crates, subfloor, trusses


### TECHNICAL SPECIFICATIONS

Collation angle	34 °
Collation type	Paper collated
Wire material	Carbon steel standard tensile
Finish	Bright basic standard tensile
Coating	Sencoted
Nail head type	Clipped head
Head width	6.71 - 7.21 mm
Head length	5 - 5.36 mm
Nail shank type	Smooth shank
Point type	Diamond
Pointangle	40 °
Nail length	90 mm
Nail diameter	3.1 mm

### LOGISTICAL SPECIFICATIONS

GTIN	8715274028576
Package quantity	2000 pieces
Net weight	10.53 kg

### FASTENER SPECIFICATIONS



### CE SPECIFICATIONS

Dit veld moet nog verwijderd worden	EN 14592:2008+A1:2012 worden
CE fastener type	Round cross-section plain shank nail
Service class	1
Coating type	Coating type 3
Coating length	60 mm
Head cross sectional area	30 mm
Characteristic yield moment	2570 Nmm
Dit veld moet nog verwijderd worden	3.1 N/mm <sup>2</sup> worden
Characteristic head pull through parameter	30.1 N/mm <sup>2</sup>
Characteristic tensile strength	633 N/mm <sup>2</sup>